

単位:mm

呼び径		適用管 の外径	共通部分						
			外径	厚み	ガスケット座		ボルト穴		
					D	t	座厚	座径	中心径
(A)	(B)			f	g	C			
10	3/8	17.3	90	12	1	46	65	4	15
15	1/2	21.7	95	12	1	51	70	4	15
20	3/4	27.2	100	14	1	56	75	4	15
25	1	34.0	125	14	1	67	90	4	19
32	1 1/4	42.7	135	16	2	76	100	4	19
40	1 1/2	48.6	140	16	2	81	105	4	19
50	2	60.5	155	16	2	96	120	4	19
65	2 1/2	76.3	175	18	2	116	140	4	19
80	3	89.1	185	18	2	126	150	8	19
90	3 1/2	101.6	195	18	2	136	160	8	19
100	4	114.3	210	18	2	151	175	8	19
125	5	139.8	250	20	2	182	210	8	23
150	6	165.2	280	22	2	212	240	8	23
175	7	190.7	305	22	2	237	265	12	23
200	8	216.3	330	22	2	262	290	12	23
225	9	241.8	350	22	2	282	310	12	23
250	10	267.4	400	24	2	324	355	12	25
300	12	318.5	445	24	3	368	400	16	25
350	14	355.6	490	26	3	413	445	16	25
400	16	406.4	560	28	3	475	510	16	27
450	18	457.2	620	30	3	530	565	20	27
500	20	508.0	675	30	3	585	620	20	27
550	22	558.8	745	32*	3	640	680	20	33
600	24	609.6	795	32*	3	690	730	24	33
650	26	660.4	845	34*	3	740	780	24	33
700	28	711.2	905	34*	3	800	840	24	33
750	30	762.0	970	36*	3	855	900	24	33
800	32	812.8	1020	36*	3	905	950	28	33
850	34	863.6	1070	36*	3	955	1000	28	33
900	36	914.4	1120	38*	3	1005	1050	28	33
1000	40	1016.0	1235	40*	3	1110	1160	28	39
1100	44	1117.6	1345	42*	3	1220	1270	28	39
1200	48	1219.2	1465	44*	3	1325	1380	32	39
1350	54	1371.6	1630	48*	3	1480	1540	36	45
1500	60	1524.0	1795	50*	3	1635	1700	40	45

※閉止フランジ(BL)の厚み(t)

呼び径	550	600	650	700	750	800	850	900	1000	1100	1200	1350	1500
厚み t	34	36	38	40	44	46	48	50	56	62	66	74	82

単位:mm

SOP形及びSOH形							重量(kg)				呼び径	
内径	全長	ハブ部			LJ		SOP	BL	SOH	LJ	(A)	(B)
		ハブ先	ハブ元	半径	内径	面取り						
do	T	a	b	r	do	Co						
17.8	—	—	—	—	—	—	0.51	0.53	—	—	10	3/8
22.2	—	—	—	—	23.4	3	0.56	0.60	—	0.56	15	1/2
27.7	—	—	—	—	28.9	3	0.72	0.79	—	0.71	20	3/4
34.5	—	—	—	—	35.6	3	1.12	1.22	—	1.11	25	1
43.2	—	—	—	—	44.3	4	1.47	1.66	—	1.45	32	1 1/4
49.1	—	—	—	—	50.4	4	1.55	1.79	—	1.53	40	1 1/2
61.1	—	—	—	—	62.7	4	1.86	2.23	—	1.83	50	2
77.1	—	—	—	—	78.7	5	2.58	3.24	—	2.53	65	2 1/2
90.0	—	—	—	—	91.6	5	2.58	3.48	—	2.52	80	3
102.6	—	—	—	—	104.1	5	2.73	3.90	—	2.66	90	3 1/2
115.4	—	—	—	—	116.9	5	3.10	4.57	—	3.02	100	4
141.2	—	—	—	—	143.0	6	4.73	7.18	—	4.60	125	5
166.6	—	—	—	—	168.4	6	6.30	10.1	—	6.14	150	6
192.1	—	—	—	—	—	—	6.75	11.8	—	—	175	7
218.0	—	—	—	—	219.5	6	7.46	13.9	—	7.28	200	8
243.7	—	—	—	—	—	—	7.70	15.8	—	—	225	9
269.5	36	288	292	6	271.7	6	11.8	22.6	12.7	12.3	250	10
321.0	38	340	346	6	322.8	9	12.6	27.8	13.8	13.2	300	12
358.1	42	380	386	6	360.2	9	16.3	36.9	18.2	17.4	350	14
409.0	44	436	442	6	411.2	9	23.2	52.1	25.8	24.8	400	16
460.0	48	496	502	6	462.3	9	29.3	68.4	33.4	32.3	450	18
511.0	48	548	554	6	514.4	9	33.3	81.6	38.0	36.4	500	20
562.0	52	604	610	6	565.2	9	42.9	112	49.4	47.7	550	22
613.0	52	656	662	6	616.0	9	45.4	134	52.6	50.8	600	24
664.0	56	706	712	6	—	—	51.8	161	60.2	—	650	26
715.0	58	762	770	6	—	—	59.0	196	70.2	—	700	28
766.0	62	816	824	6	—	—	72.8	248	86.5	—	750	30
817.0	64	868	876	6	—	—	76.0	286	92.0	—	800	32
868.0	66	920	928	6	—	—	80.1	330	98.7	—	850	34
919.0	70	971	979	6	—	—	88.9	377	110	—	900	36
1021.0	74	1073	1081	6	—	—	109	512	133	—	1000	40
1122.0	95	1175	1185	8	—	—	131	675	175	—	1100	44
1224.0	101	1278	1290	8	—	—	163	854	215	—	1200	48
1376.0	110	1432	1450	8	—	—	204	1180	274	—	1350	54
1529.0	123	1585	1605	8	—	—	248	1590	340	—	1500	60

備考 1. JIS B 2220 は呼び径(A)10～1500のSOP形FFとBL形FF、呼び径(A)250～1500のSOH形FF、呼び径(A)15～600のLJ形を規定しており、他はJIS B 2238の基準寸法による。
 2. LJのコーナー(Co)はC面及びR面どちらでもよい。