

単位:mm									
呼び径		適用管 の外径	共通部分						
			外径	厚み	ガスケット座		ボルト穴		
					座厚	座径	中心径	数	h
(A)	(B)		D	t	f	g	C		
10	$\frac{3}{8}$	17.3	90	12	1	46	65	4	15
15	$\frac{1}{2}$	21.7	95	12	1	51	70	4	15
20	$\frac{3}{4}$	27.2	100	14	1	56	75	4	15
25	1	34.0	125	14	1	67	90	4	19
32	$1\frac{1}{4}$	42.7	135	16	2	76	100	4	19
40	$1\frac{1}{2}$	48.6	140	16	2	81	105	4	19
50	2	60.5	155	16	2	96	120	8	19
65	$2\frac{1}{2}$	76.3	175	18	2	116	140	8	19
80	3	89.1	200	20	2	132	160	8	23
90	$3\frac{1}{2}$	101.6	210	20	2	145	170	8	23
100	4	114.3	225	22	2	160	185	8	23
125	5	139.8	270	22	2	195	225	8	25
150	6	165.2	305	24	2	230	260	12	25
200	8	216.3	350	26	2	275	305	12	25
250	10	267.4	430	28	2	345	380	12	27
300	12	318.5	480	30	3	395	430	16	27
350	14	355.6	540	34	3	440	480	16	33
400	16	406.4	605	38	3	495	540	16	33
450	18	457.2	675	40	3	560	605	20	33
500	20	508.0	730	42	3	615	660	20	33
550	22	558.8	795	44	3	670	720	20	39
600	24	609.6	845	46	3	720	770	24	39
650	26	660.4	895	48	5	770	820	24	39
700	28	711.2	960	50	5	820	875	24	42
750	30	762.0	1020	52	5	880	935	24	42
800	32	812.8	1085	54	5	930	990	24	48
850	34	863.6	1135	56	5	980	1040	24	48
900	36	914.4	1185	58	5	1030	1090	28	48
1000	40	1016.0	1320	62	5	1140	1210	28	56
1100	44	1117.6	1420	66	5	1240	1310	32	56
1200	48	1219.2	1530	70	5	1350	1420	32	56
1350	54	1371.6	1700	76	5	1510	1590	32	62
1500	60	1524.0	1865	80	5	1670	1750	36	62

備考 1. JIS B 2220 は、呼び径(A)10 ～ 600 の SOH 形 FF と BL 形 FF を規定しており、他は JIS B 2238 の基準寸法による。

単位:mm

SOP 形及び SOH 形					重量(kg)			呼び径	
内径	全長	ハブ部							
		ハブ先	ハブ元	半径	SOP	BL	SOH	(A)	(B)
do	T	a	b	r					
17.8	16	26	28	4	0.51	0.53	0.52	10	$\frac{3}{8}$
22.2	16	30	32	4	0.56	0.60	0.58	15	$\frac{1}{2}$
27.7	20	38	42	4	0.72	0.79	0.75	20	$\frac{3}{4}$
34.5	20	46	50	4	1.13	1.22	1.16	25	1
43.2	22	56	60	5	1.46	1.66	1.53	32	$1\frac{1}{4}$
49.1	24	62	66	5	1.56	1.79	1.64	40	$1\frac{1}{2}$
61.1	24	76	80	5	1.7	2.09	1.83	50	2
77.1	26	94	98	5	2.4	3.08	2.58	65	$2\frac{1}{2}$
90.0	28	108	112	6	3.5	4.41	3.61	80	3
102.6	30	120	124	6	3.7	4.92	3.89	90	$3\frac{1}{2}$
115.4	34	134	138	6	4.5	6.29	4.87	100	4
141.2	34	164	170	6	6.5	9.21	7.09	125	5
166.6	38	196	202	6	8.7	12.7	9.57	150	6
218.0	40	244	252	6	10.9	18.4	12.0	200	8
269.5	44	304	312	6	18.0	30.4	20.1	250	10
321.0	48	354	364	8	21.5	40.5	24.3	300	12
358.1	52	398	408	8	30.8	57.5	34.4	350	14
409	60	446	456	10	42.8	81.7	47.4	400	16
460	64	504	514	10	55.1	107	61.8	450	18
511	68	558	568	10	65.1	132	73.7	500	20
562	70	612	622	10	77.9	163	87.9	550	22
613	74	666	676	10	86.0	192	98.4	600	24
664	77	704	726	10	96.3	227	101	650	26
715	80	754	776	10	114.1	272	120	700	28
766	83	806	832	10	132.7	321	141	750	30
817	86	865	885	10	152.1	375	161	800	32
868	89	916	936	10	166.5	428	177	850	34
919	93	968	986	10	178.1	481	191	900	36
1021	99	1070	1098	12	235.3	636	230	1000	40
1122	105	1180	1200	12	267.9	784	289	1100	44
1224	112	1282	1302	12	321.1	972	348	1200	48
1376	—	—	—	—	410.0	1303	—	1350	54
1529	—	—	—	—	496.4	1656	—	1500	60