


キャップ



SW Sch80

単位:mm

呼び径(A)	呼び径(B)	S	C	H	B	K	T
6	1/8	11	10	16	18	3.5	2.7
8	1/4	14.3	10	17	22	4.5	3.3
10	3/8	17.8	10	17.5	26	5	3.5
15	1/2	22.2	10	18.6	32	6.1	4.1
20	3/4	27.7	13	22.5	38	7	4.3
25	1	34.5	13	23.8	46	8.3	5
32	1 1/4	43.2	13	26.6	55	9.6	5.4
40	1 1/2	49.1	13	27.5	65	10.5	5.6
50	2	61.1	16	32.2	75	12.2	6.1
65	2 1/2	77.1	16	35.3	95	15.3	7.7
80	3	90	16	37.3	110	17	8.4

SW Sch160

単位:mm

呼び径(A)	呼び径(B)	S	C	H	B	K	T
15	1/2	22.2	10	19.7	38	7.2	5.2
20	3/4	27.7	13	24.3	46	8.8	6.1
25	1	34.5	13	27.6	50	10.6	7
32	1 1/4	43.2	13	28.8	60	11.8	7
40	1 1/2	49.1	13	30.3	70	13.3	7.8
50	2	61.1	16	36.4	85	16.4	9.6
65	2 1/2	77.1	16	39.2	100	19.2	10.4
80	3	90	16	42.5	120	22.5	12.2

※K 寸法は ASME B16.11 による。