



溶接用エキセントレジャーサー T-14



単位:mm

| サイズ | D1 | d1 | D2 | d2 | L | T-13 重量(kg) |
|-----------|-------|-------|-------|------|-------|-------------|
| 10A× 8A | 17.3 | 14.0 | 13.8 | 10.5 | 14.0 | 0.01 |
| 15A× 8A | 21.7 | 18.4 | 13.8 | 10.5 | 24.0 | 0.02 |
| 15A×10A | 21.7 | 18.4 | 17.3 | 14.0 | 19.0 | 0.01 |
| 1.0S× 8A | 25.4 | 23.0 | 13.8 | 10.5 | 38.0 | 0.03 |
| 1.0S×10A | 25.4 | 23.0 | 17.3 | 14.0 | 38.0 | 0.03 |
| 1.0S×15A | 25.4 | 23.0 | 21.7 | 18.4 | 38.0 | 0.03 |
| 1.5S× 8A | 38.1 | 35.7 | 13.8 | 10.5 | 38.0 | 0.03 |
| 1.5S×10A | 38.1 | 35.7 | 17.3 | 14.0 | 38.0 | 0.04 |
| 1.5S×15A | 38.1 | 35.7 | 21.7 | 18.4 | 38.0 | 0.05 |
| 1.5S×1.0S | 38.1 | 35.7 | 25.4 | 23.0 | 67.0 | 0.07 |
| 2.0S×1.0S | 50.8 | 47.8 | 25.4 | 23.0 | 67.0 | 0.10 |
| 2.0S×1.5S | 50.8 | 47.8 | 38.1 | 35.7 | 67.0 | 0.11 |
| 2.5S×1.0S | 63.5 | 59.5 | 25.4 | 23.0 | 67.0 | 0.13 |
| 2.5S×1.5S | 63.5 | 59.5 | 38.1 | 35.7 | 67.0 | 0.18 |
| 2.5S×2.0S | 63.5 | 59.5 | 50.8 | 47.8 | 67.0 | 0.20 |
| 3.0S×1.0S | 76.3 | 72.3 | 25.4 | 23.0 | 67.0 | 0.16 |
| 3.0S×1.5S | 76.3 | 72.3 | 38.1 | 35.7 | 67.0 | 0.23 |
| 3.0S×2.0S | 76.3 | 72.3 | 50.8 | 47.8 | 67.0 | 0.24 |
| 3.0S×2.5S | 76.3 | 72.3 | 63.5 | 59.5 | 67.0 | 0.24 |
| 3.5S×2.0S | 89.1 | 85.1 | 50.8 | 47.8 | 90.0 | 0.27 |
| 3.5S×2.5S | 89.1 | 85.1 | 63.5 | 59.5 | 90.0 | 0.34 |
| 3.5S×3.0S | 89.1 | 85.1 | 76.3 | 72.3 | 90.0 | 0.35 |
| 4.0S×1.5S | 101.6 | 97.6 | 38.1 | 35.7 | 102.0 | 0.35 |
| 4.0S×2.0S | 101.6 | 97.6 | 50.8 | 47.8 | 120.0 | 0.45 |
| 4.0S×2.5S | 101.6 | 97.6 | 63.5 | 59.5 | 120.0 | 0.51 |
| 4.0S×3.0S | 101.6 | 97.6 | 76.3 | 72.3 | 102.0 | 0.48 |
| 4.0S×3.5S | 101.6 | 97.6 | 89.1 | 85.1 | 120.0 | 0.55 |
| 4.5S×4.0S | 114.3 | 108.3 | 101.6 | 97.6 | 130.0 | 0.86 |
| 5.0S×4.0S | 139.8 | 133.8 | 101.6 | 97.6 | 160.0 | 1.27 |

※概算重量としてT-14はT-13を参考にして下さい。