


# ヘルール付コンセントレジュサー 31-14MD



単位:mm

サイズ	C1	P1	d1	C2	P2	d2	L	31-14MD重量(kg)
10A× 8A	34.0	27.5	14.0	34.0	27.5	10.5	48.0	0.07
15A× 8A	34.0	27.5	18.4	34.0	27.5	10.5	58.0	0.08
15A×10A	34.0	27.5	18.4	34.0	27.5	14.0	53.0	0.08
1.0S× 8A	50.5	43.5	23.0	34.0	27.5	10.5	75.0	0.14
1.0S×10A	50.5	43.5	23.0	34.0	27.5	14.0	75.0	0.14
1.0S×15A	50.5	43.5	23.0	34.0	27.5	18.4	75.0	0.14
1.5S× 8A	50.5	43.5	35.7	34.0	27.5	10.5	75.0	0.13
1.5S×10A	50.5	43.5	35.7	34.0	27.5	14.0	75.0	0.13
1.5S×15A	50.5	43.5	35.7	34.0	27.5	18.4	75.0	0.12
1.5S×1.0S	50.5	43.5	35.7	50.5	43.5	23.0	107.0	0.18
2.0S×1.0S	64.0	56.5	47.8	50.5	43.5	23.0	107.0	0.24
2.0S×1.5S	64.0	56.5	47.8	50.5	43.5	35.7	107.0	0.22
2.5S×1.0S	77.5	70.5	59.5	50.5	43.5	23.0	107.0	0.32
2.5S×1.5S	77.5	70.5	59.5	50.5	43.5	35.7	107.0	0.30
2.5S×2.0S	77.5	70.5	59.5	64.0	56.5	47.8	107.0	0.35
3.0S×1.0S	91.0	83.5	72.3	50.5	43.5	23.0	107.0	0.39
3.0S×1.5S	91.0	83.5	72.3	50.5	43.5	35.7	107.0	0.23
3.0S×2.0S	91.0	83.5	72.3	64.0	56.5	47.8	107.0	0.41
3.0S×2.5S	91.0	83.5	72.3	77.5	70.5	59.5	107.0	0.49
3.5S×2.0S	106.0	97.0	85.1	64.0	56.5	47.8	130.0	0.56
3.5S×2.5S	106.0	97.0	85.1	77.5	70.5	59.5	130.0	0.64
3.5S×3.0S	106.0	97.0	85.1	91.0	83.5	72.3	130.0	0.67
4.0S×1.5S	119.0	110.0	97.6	50.5	43.5	35.7	149.0	0.65
4.0S×2.0S	119.0	110.0	97.6	64.0	56.5	47.8	167.0	0.78
4.0S×2.5S	119.0	110.0	97.6	77.5	70.5	59.5	167.0	0.87
4.0S×3.0S	119.0	110.0	97.6	91.0	83.5	72.3	149.0	0.83
4.0S×3.5S	119.0	110.0	97.6	106.0	97.0	85.1	167.0	0.97
4.5S×4.0S	130.0	122.0	108.3	119.0	110.0	97.6	184.0	1.41
5.0S×4.0S	155.0	146.0	133.8	119.0	110.0	97.6	214.0	1.98

※概算重量として 32-14MDは上記 31-14MDを参考にして下さい。