


# ラップジョイント LJ (JIS タイプ 5K・10K)



5K



10K



単位:mm

単位:kg

呼び径		外径	厚み			ツバ径 G		長さ	概略重量 (JIS 10K の場合)		
(A)	(B)	OD	Sch10S	Sch20S	Sch40	5K	10K	F	Sch10S	Sch20S	Sch40
10	⅜	17.3	1.65	2.0	2.3	39	46	30	0.1	0.1	0.1
15	½	21.7	2.1	2.5	2.8	44	51	30	0.1	0.1	0.1
20	¾	27.2	2.1	2.5	2.9	49	56	30	0.1	0.1	0.1
25	1	34.0	2.8	3.0	3.4	59	67	50	0.2	0.2	0.2
32	1¼	42.7	2.8	3.0	3.6	70	76	50	0.2	0.2	0.3
40	1½	48.6	2.8	3.0	3.7	75	81	50	0.2	0.3	0.3
50	2	60.5	2.8	3.5	3.9	85	96	50	0.3	0.4	0.4
65	2½	76.3	3.0	3.5	5.2	110	116	50	0.4	0.5	0.7
80	3	89.1	3.0	4.0	5.5	121	126	50	0.5	0.6	0.9
90	3½	101.6	3.0	4.0	5.7	131	136	50	0.5	0.7	1.0
100	4	114.3	3.0	4.0	6.0	141	151	50	0.6	0.8	1.2
125	5	139.8	3.4	5.0	6.6	176	182	50	0.9	1.3	1.7
150	6	165.2	3.4	5.0	7.1	206	212	50	1.1	1.6	2.2
200	8	216.3	4.0	6.5	8.2	252	262	65	1.9	3.1	3.9
250	10	267.4	4.0	6.5	9.3	317	324	65	2.5	4.1	5.8
300	12	318.5	4.5	6.5	10.3	360	368	65	3.3	4.7	7.3
350	14	355.6	5.0	8.0	11.1	403	413	75	4.7	7.4	10.2
400	16	406.4	5.0	8.0	12.7	463	475	75	5.6	9.0	14.2
450	18	457.2	5.0	8.0	14.3	523	530	75	6.5	10.3	18.3
500	20	508.0	5.5	9.5	15.1	573	585	75	8.1	13.9	21.9
550	22	558.8	5.5	9.5	15.9	630	640	75	9.0	15.5	25.8
600	24	609.6	6.5	9.5	17.5	680	690	75	11.6	16.9	30.8

※JPI 規格の取り扱いもございます。