


同芯レジャーサー R(C)



呼び径				外径		厚み				端面から 端面までの 距離H	概略重量				
(A)		(B)				Sch10S		Sch20S		Sch40		Sch10S	Sch20S	Sch40	
OD①	OD②	OD①	OD②	OD①	OD②	①	②	①	②	①	②				
15	10	1/2	3/8	21.7	17.3	2.1	1.65	2.5	2.0	2.8	2.3	38.1	0.1	0.1	0.1
20	15	3/4	1/2	27.2	21.7	2.1	2.1	2.5	2.5	2.9	2.8	38.1	0.1	0.1	0.1
	10	3/4	3/8	27.2	17.3	2.1	1.65	2.5	2.0	2.9	2.3	38.1	0.1	0.1	0.1
25	20		3/4	34.0	27.2	2.8	2.1	3.0	2.5	3.4	2.9	50.8	0.1	0.1	0.1
	15	1	1/2	34.0	21.7	2.8	2.1	3.0	2.5	3.4	2.8	50.8	0.1	0.1	0.1
32	10		3/8	34.0	17.3	2.8	1.65	3.0	2.0	3.4	2.3	50.8	0.1	0.1	0.1
	25	1	1	42.7	34.0	2.8	2.8	3.0	3.0	3.6	3.4	50.8	0.1	0.1	0.2
40	20	1 1/4	3/4	42.7	27.2	2.8	2.1	3.0	2.5	3.6	2.9	50.8	0.1	0.1	0.1
	15		1/2	42.7	21.7	2.8	2.1	3.0	2.5	3.6	2.8	50.8	0.1	0.1	0.1
50	10		3/8	42.7	17.3	2.8	1.65	3.0	2.0	3.6	2.3	50.8	0.1	0.1	0.1
	32	1 1/4	1/4	48.6	42.7	2.8	2.8	3.0	3.0	3.7	3.6	63.5	0.2	0.2	0.2
65	25	1 1/2	1	48.6	34.0	2.8	2.8	3.0	3.0	3.7	3.4	63.5	0.2	0.2	0.2
	20		3/4	48.6	27.2	2.8	2.1	3.0	2.5	3.7	2.9	63.5	0.2	0.2	0.2
80	15		1/2	48.6	21.7	2.8	2.1	3.0	2.5	3.7	2.8	63.5	0.1	0.2	0.2
	40	2	1 1/2	60.5	48.6	2.8	2.8	3.5	3.0	3.9	3.7	76.2	0.3	0.3	0.4
90	32		1 1/4	60.5	42.7	2.8	2.8	3.5	3.0	3.9	3.6	76.2	0.3	0.3	0.4
	25	2	1	60.5	34.0	2.8	2.8	3.5	3.0	3.9	3.4	76.2	0.2	0.3	0.3
100	20		3/4	60.5	27.2	2.8	2.1	3.5	2.5	3.9	2.9	76.2	0.2	0.3	0.3
	15		1/2	60.5	21.7	2.8	2.1	3.5	2.5	3.9	2.8	76.2	0.2	0.3	0.3
125	50	2 1/2	2	76.3	60.5	3.0	2.8	3.5	3.5	5.2	3.9	88.9	0.4	0.5	0.7
	40		1 1/2	76.3	48.6	3.0	2.8	3.5	3.0	5.2	3.7	88.9	0.4	0.5	0.7
150	32	2 1/2	1 1/4	76.3	42.7	3.0	2.8	3.5	3.0	5.2	3.6	88.9	0.4	0.4	0.6
	25	3	1	76.3	34.0	3.0	2.8	3.5	3.0	5.2	3.4	88.9	0.4	0.4	0.6
200	65	3 1/2	2 1/2	89.1	76.3	3.0	3.0	4.0	3.5	5.5	5.2	88.9	0.5	0.7	0.9
	50		2	89.1	60.5	3.0	2.8	4.0	3.5	5.5	3.9	88.9	0.5	0.6	0.9
250	40	3	1 1/2	89.1	48.6	3.0	2.8	4.0	3.0	5.5	3.7	88.9	0.4	0.6	0.8
	32		1 1/4	89.1	42.7	3.0	2.8	4.0	3.0	5.5	3.6	88.9	0.4	0.6	0.8
300	25	3	1	89.1	34.0	3.0	2.8	4.0	3.0	5.5	3.4	88.9	0.4	0.5	0.7
	80	3	3	101.6	89.1	3.0	3.0	4.0	4.0	5.7	5.5	101.6	0.7	0.9	1.3
350	65	3 1/2	2 1/2	101.6	76.3	3.0	3.0	4.0	3.5	5.7	5.2	101.6	0.7	0.9	1.2
	50		2	101.6	60.5	3.0	2.8	4.0	3.5	5.7	3.9	101.6	0.6	0.8	1.1
400	40	4	1 1/2	101.6	48.6	3.0	2.8	4.0	3.0	5.7	3.7	101.6	0.6	0.7	1.0
	90	3 1/2	3	114.3	101.6	3.0	3.0	4.0	4.0	6.0	5.7	101.6	0.8	1.1	1.6
450	80	4	3	114.3	89.1	3.0	3.0	4.0	4.0	6.0	5.5	101.6	0.8	1.0	1.5
	65		2 1/2	114.3	76.3	3.0	3.0	4.0	3.5	6.0	5.2	101.6	0.7	0.9	1.4
500	50	4	2	114.3	60.5	3.0	2.8	4.0	3.5	6.0	3.9	101.6	0.7	0.9	1.3
	40		1 1/2	114.3	48.6	3.0	2.8	4.0	3.0	6.0	3.7	101.6	0.6	0.8	1.2
550	100	5	4	139.8	114.3	3.4	3.0	5.0	4.0	6.6	6.0	127.0	1.3	1.9	2.5
	90		3 1/2	139.8	101.6	3.4	3.0	5.0	4.0	6.6	5.7	127.0	1.3	1.9	2.4
600	80	5	3	139.8	89.1	3.4	3.0	5.0	4.0	6.6	5.5	127.0	1.2	1.8	2.3
	65		2 1/2	139.8	76.3	3.4	3.0	5.0	3.5	6.6	5.2	127.0	1.2	1.7	2.2
650	50	6	2	139.8	60.5	3.4	2.8	5.0	3.5	6.6	3.9	127.0	1.1	1.6	2.1
	125	5	4	165.2	139.8	3.4	3.4	5.0	5.0	7.1	6.6	139.7	1.8	2.6	3.6
700	100	6	4	165.2	114.3	3.4	3.0	5.0	4.0	7.1	6.0	139.7	1.6	2.4	3.3
	90		3 1/2	165.2	101.6	3.4	3.0	5.0	4.0	7.1	5.7	139.7	1.6	2.3	3.2
750	80	6	3	165.2	89.1	3.4	3.0	5.0	4.0	7.1	5.5	139.7	1.5	2.2	3.1
	65		2 1/2	165.2	76.3	3.4	3.0	5.0	3.5	7.1	5.2	139.7	1.5	2.1	3.0
800	150	8	6	216.3	165.2	4.0	3.4	6.5	5.0	8.2	7.1	152.4	2.9	4.6	5.8
	125		5	216.3	139.8	4.0	3.4	6.5	5.0	8.2	6.6	152.4	2.7	4.4	5.5
850	100	8	4	216.3	114.3	4.0	3.0	6.5	4.0	8.2	6.0	152.4	2.6	4.1	5.2
	200	8	8	267.4	216.3	4.0	4.0	6.5	6.5	9.3	8.2	177.8	4.3	6.9	9.7
900	150	10	6	267.4	165.2	4.0	3.4	6.5	5.0	9.3	7.1	177.8	3.9	6.3	8.9
	125		5	267.4	139.8	4.0	3.4	6.5	5.0	9.3	6.6	177.8	3.8	6.0	8.5
950	100	10	4	267.4	114.3	4.0	3.0	6.5	4.0	9.3	6.0	177.8	3.6	5.8	8.2
	250	10	10	318.5	267.4	4.5	4.0	6.5	6.5	10.3	9.3	203.2	6.6	9.5	14.9
1000	200	12	8	318.5	216.3	4.5	4.0	6.5	6.5	10.3	8.2	203.2	6.2	8.9	13.9
	150		6	318.5	165.2	4.5	3.4	6.5	5.0	10.3	7.1	203.2	5.8	8.3	12.9
1050	300	14	12	355.6	318.5	5.0	4.5	8.0	6.5	11.1	10.3	330.2	13.7	21.7	29.9
	250		10	355.6	267.4	5.0	4.0	8.0	6.5	11.1	9.3	330.2	12.7	20.2	27.7
1100	200	14	8	355.6	216.3	5.0	4.0	8.0	6.5	11.1	8.2	330.2	11.8	18.7	25.7
	150		6	355.6	165.2	5.0	3.4	8.0	5.0	11.1	7.1	330.2	10.9	17.3	23.7
1150	350	16	14	406.4	355.6	5.0	5.0	8.0	8.0	12.7	11.1	355.6	16.7	26.6	41.6
	300		12	406.4	318.5	5.0	4.5	8.0	6.5	12.7	10.3	355.6	16.0	25.4	39.7
1200	250	16	10	406.4	267.4	5.0	4.0	8.0	6.5	12.7	9.3	355.6	15.0	23.8	37.2
	200		8	406.4	216.3	5.0	4.0	8.0	6.5	12.7	8.2	355.6	14.1	22.3	34.8
1250	400	18	16	457.2	406.4	5.0	5.0	8.0	8.0	14.3	12.7	381.0	20.3	32.3	56.9
	350		14	457.2	355.6	5.0	5.0	8.0	8.0	14.3	11.1	381.0	19.2	30.6	53.8
1300	300	18	12	457.2	318.5	5.0	4.5	8.0	6.5	14.3	10.3	381.0	18.5	29.4	51.6
	250		10	457.2	267.4	5.0	4.0	8.0	6.5	14.3	9.3	381.0	17.5	27.8	48.8
1350	450	20	18	508.0	457.2	5.5	5.0	9.5	8.0	15.1	14.3	508.0	33.3	57.1	89.6
	400		16	508.0	406.4	5.5	5.0	9.5	8.0	15.1	12.7	508.0	31.6	54.2	85.1
1400	350	20	14	508.0	355.6	5.5	5.0	9.5	8.0	15.1	11.1	508.0	30.0	51.4	80.7
	300		12	508.0	318.5	5.5	4.5	9.5	6.5	15.1	10.3	508.0	28.9	49.5	77.5
1450	500	22	20	558.8	508.0	5.5	5.5	9.5	9.5	15.9	15.1	508.0	36.8	63.2	104.5
	450		18	558.8	457.2	5.5	5.0	9.5	8.0	15.9	14.3	508.0	35.2	60.3	99.7
1500	400	22	16	558.8	406.4	5.5	5.0	9.5	8.0	15.9	12.7	508.0	33.6	57.6	95.1
	350		14	558.8	355.6	5.5	5.0	9.5	8.0	15.9	11.1	508.0	32.1	55.0	90.7
1550	550	24	22	609.6	558.8	6.5	5.5	9.5	9.5	17.5	15.9	508.0	47.6	69.3	125.9
	500		20	609.6	508.0	6.5	5.5	9.5	9.5	17.5	15.1	508.0	45.7	66.5	120.7
1600	450	24	18	609.6	457.2	6.5	5.0	9.5	8.0	17.5	14.3	508.0	43.9	63.8	115.8
	400		16	609.6	406.4	6.5	5.0	9.5	8.0	17.5	12.7	508.0	42.1	61.2	111.0
1650	600	26	24	660.4	609.6	8.0	6.5	12.7	9.5	—	—	609.6	76.3	120.4	—
	550		22	660.4	558.8	8.0	5.5	12.7	9.5	—	—	609.6	73.4	115.7	—
1700	500		20	660.4	508.0	8.0	5.5	12.7	9.5	—	—	609.6	70.6	111.3	—
	450		18	660.4	457.2	8.0	5.0	12.7	8.0	—	—	609.6	67.9	107.0	—
1750	650	28	26	711.2	660.4	8.0	8.0	12.7	12.7	—	—	609.6	82.5	130.2	—
	600		24	711.2	609.6	8.0	6.5	12.7	9.5	17.5	17.5	609.6	79.6	125.6	171.8
1800	550		22	711.2	558.8	8.0	5.5	12.7	9.5	17.5	15.9	609.6	76.8	121.2	165.7
	500		20	711.2	508.0	8.0	5.5	12.7	9.5	17.5	15.9	609.6	74.2	116.	