


偏芯レジャーサー R(E)



呼び径		外径		厚み		Sch10S		Sch20S		Sch40		端面から 端面までの 距離 H	概略重量		
(A)	(B)	OD①	OD②	①	②	①	②	①	②	Sch10S	Sch20S		Sch40		
15	10	1/2	3/8	21.7	17.3	2.1	1.65	2.5	2.0	2.8	2.3	38.1	0.1	0.1	0.1
15	15	3/4	1/2	27.2	21.7	2.1	2.1	2.5	2.5	2.9	2.8	38.1	0.1	0.1	0.1
20	10	3/4	3/8	27.2	17.3	2.1	1.65	2.5	2.0	2.9	2.3	38.1	0.1	0.1	0.1
20	20	1	3/4	34.0	27.2	2.8	2.1	3.0	2.5	3.4	2.9	50.8	0.1	0.1	0.1
25	15	1	1/2	34.0	21.7	2.8	2.1	3.0	2.5	3.4	2.8	50.8	0.1	0.1	0.1
25	20	1	3/8	34.0	17.3	2.8	1.65	3.0	2.0	3.4	2.3	50.8	0.1	0.1	0.1
25	25	1	1	42.7	34.0	2.8	2.8	3.0	3.0	3.6	3.4	50.8	0.1	0.1	0.2
32	20	1 1/4	3/4	42.7	27.2	2.8	2.1	3.0	2.5	3.6	2.9	50.8	0.1	0.1	0.1
32	15	1 1/4	1/2	42.7	21.7	2.8	2.1	3.0	2.5	3.6	2.8	50.8	0.1	0.1	0.1
32	10	1 1/4	3/8	42.7	17.3	2.8	1.65	3.0	2.0	3.6	2.3	50.8	0.1	0.1	0.1
32	32	1 1/4	1 1/4	48.6	42.7	2.8	2.8	3.0	3.0	3.7	3.6	63.5	0.2	0.2	0.2
40	25	1 1/2	1	48.6	34.0	2.8	2.8	3.0	3.0	3.7	3.4	63.5	0.2	0.2	0.2
40	20	1 1/2	3/4	48.6	27.2	2.8	2.1	3.0	2.5	3.7	2.9	63.5	0.2	0.2	0.2
40	15	1 1/2	1/2	48.6	21.7	2.8	2.1	3.0	2.5	3.7	2.8	63.5	0.1	0.2	0.2
40	40	1 1/2	1 1/2	60.5	48.6	2.8	2.8	3.5	3.0	3.9	3.7	76.2	0.3	0.3	0.4
50	32	2	1 1/4	60.5	42.7	2.8	2.8	3.5	3.0	3.9	3.6	76.2	0.3	0.3	0.4
50	25	2	1	60.5	34.0	2.8	2.8	3.5	3.0	3.9	3.4	76.2	0.2	0.3	0.3
50	20	2	3/4	60.5	27.2	2.8	2.1	3.5	2.5	3.9	2.9	76.2	0.2	0.3	0.3
50	15	2	1/2	60.5	21.7	2.8	2.1	3.5	2.5	3.9	2.8	76.2	0.2	0.3	0.3
50	50	2	2	76.3	60.5	3.0	2.8	3.5	3.5	5.2	3.9	88.9	0.4	0.5	0.7
65	40	2 1/2	1 1/2	76.3	48.6	3.0	2.8	3.5	3.0	5.2	3.7	88.9	0.4	0.5	0.7
65	32	2 1/2	1 1/4	76.3	42.7	3.0	2.8	3.5	3.0	5.2	3.6	88.9	0.4	0.4	0.6
65	25	2 1/2	1	76.3	34.0	3.0	2.8	3.5	3.0	5.2	3.4	88.9	0.4	0.4	0.6
65	65	2 1/2	2 1/2	89.1	76.3	3.0	3.0	4.0	3.5	5.5	5.2	88.9	0.5	0.7	0.9
80	50	3	2	89.1	60.5	3.0	2.8	4.0	3.5	5.5	3.9	88.9	0.5	0.6	0.9
80	40	3	1 1/2	89.1	48.6	3.0	2.8	4.0	3.0	5.5	3.7	88.9	0.4	0.6	0.8
80	32	3	1 1/4	89.1	42.7	3.0	2.8	4.0	3.0	5.5	3.6	88.9	0.4	0.6	0.8
80	25	3	1	89.1	34.0	3.0	2.8	4.0	3.0	5.5	3.4	88.9	0.4	0.5	0.7
90	80	3 1/2	3	101.6	89.1	3.0	3.0	4.0	4.0	5.7	5.5	101.6	0.7	0.9	1.3
90	65	3 1/2	2 1/2	101.6	76.3	3.0	3.0	4.0	3.5	5.7	5.2	101.6	0.7	0.9	1.2
90	50	3 1/2	2	101.6	60.5	3.0	2.8	4.0	3.5	5.7	3.9	101.6	0.6	0.8	1.1
90	40	3 1/2	1 1/2	101.6	48.6	3.0	2.8	4.0	3.0	5.7	3.7	101.6	0.6	0.7	1.0
90	90	3 1/2	3 1/2	114.3	101.6	3.0	3.0	4.0	4.0	6.0	5.7	101.6	0.8	1.1	1.6
100	80	4	3	114.3	89.1	3.0	3.0	4.0	4.0	6.0	5.5	101.6	0.8	1.0	1.5
100	65	4	2 1/2	114.3	76.3	3.0	3.0	4.0	3.5	6.0	5.2	101.6	0.7	0.9	1.4
100	50	4	2	114.3	60.5	3.0	2.8	4.0	3.5	6.0	3.9	101.6	0.7	0.9	1.3
100	40	4	1 1/2	114.3	48.6	3.0	2.8	4.0	3.0	6.0	3.7	101.6	0.6	0.8	1.2
125	100	5	4	139.8	114.3	3.4	3.0	5.0	4.0	6.6	6.0	127.0	1.3	1.9	2.5
125	90	5	3 1/2	139.8	101.6	3.4	3.0	5.0	4.0	6.6	5.7	127.0	1.3	1.9	2.4
125	80	5	3	139.8	89.1	3.4	3.0	5.0	4.0	6.6	5.5	127.0	1.2	1.8	2.3
125	65	5	2 1/2	139.8	76.3	3.4	3.0	5.0	3.5	6.6	5.2	127.0	1.2	1.7	2.2
125	50	5	2	139.8	60.5	3.4	2.8	5.0	3.5	6.6	3.9	127.0	1.1	1.6	2.1
150	125	6	5	165.2	139.8	3.4	3.4	5.0	5.0	7.1	6.6	139.7	1.8	2.6	3.6
150	100	6	4	165.2	114.3	3.4	3.0	5.0	4.0	7.1	6.0	139.7	1.6	2.4	3.3
150	90	6	3 1/2	165.2	101.6	3.4	3.0	5.0	4.0	7.1	5.7	139.7	1.6	2.3	3.2
150	80	6	3	165.2	89.1	3.4	3.0	5.0	4.0	7.1	5.5	139.7	1.5	2.2	3.1
150	65	6	2 1/2	165.2	76.3	3.4	3.0	5.0	3.5	7.1	5.2	139.7	1.5	2.1	3.0
200	150	8	6	216.3	165.2	4.0	3.4	6.5	5.0	8.2	7.1	152.4	2.9	4.6	5.8
200	125	8	5	216.3	139.8	4.0	3.4	6.5	5.0	8.2	6.6	152.4	2.7	4.4	5.5
200	100	8	4	216.3	114.3	4.0	3.0	6.5	4.0	8.2	6.0	152.4	2.6	4.1	5.2
200	200	8	8	267.4	216.3	4.0	4.0	6.5	6.5	9.3	8.2	177.8	4.3	6.9	9.7
250	150	10	6	267.4	165.2	4.0	3.4	6.5	5.0	9.3	7.1	177.8	3.9	6.3	8.9
250	125	10	5	267.4	139.8	4.0	3.4	6.5	5.0	9.3	6.6	177.8	3.8	6.0	8.5
250	100	10	4	267.4	114.3	4.0	3.0	6.5	4.0	9.3	6.0	177.8	3.6	5.8	8.2
300	250	12	10	318.5	267.4	4.5	4.0	6.5	6.5	10.3	9.3	203.2	6.6	9.5	14.9
300	200	12	8	318.5	216.3	4.5	4.0	6.5	6.5	10.3	8.2	203.2	6.2	8.9	13.9
300	150	12	6	318.5	165.2	4.5	3.4	6.5	5.0	10.3	7.1	203.2	5.8	8.3	12.9
350	300	14	12	355.6	318.5	5.0	4.5	8.0	6.5	11.1	10.3	330.2	13.7	21.7	29.9
350	250	14	10	355.6	267.4	5.0	4.0	8.0	6.5	11.1	9.3	330.2	12.7	20.2	27.7
350	200	14	8	355.6	216.3	5.0	4.0	8.0	6.5	11.1	8.2	330.2	11.8	18.7	25.7
350	150	14	6	355.6	165.2	5.0	3.4	8.0	5.0	11.1	7.1	330.2	10.9	17.3	23.7
400	350	16	14	406.4	355.6	5.0	5.0	8.0	8.0	12.7	11.1	355.6	16.7	26.6	41.6
400	300	16	12	406.4	318.5	5.0	4.5	8.0	6.5	12.7	10.3	355.6	16.0	25.4	39.7
400	250	16	10	406.4	267.4	5.0	4.0	8.0	6.5	12.7	9.3	355.6	15.0	23.8	37.2
400	200	16	8	406.4	216.3	5.0	4.0	8.0	6.5	12.7	8.2	355.6	14.1	23.2	34.8
450	400	18	16	457.2	406.4	5.0	5.0	8.0	8.0	14.3	12.7	381.0	20.3	32.3	56.9
450	350	18	14	457.2	355.6	5.0	5.0	8.0	8.0	14.3	11.1	381.0	19.2	30.6	53.8
450	300	18	12	457.2	318.5	5.0	4.5	8.0	6.5	14.3	10.3	381.0	18.5	29.4	51.6
450	250	18	10	457.2	267.4	5.0	4.0	8.0	6.5	14.3	9.3	381.0	17.5	27.8	48.8
500	450	20	18	508.0	457.2	5.5	5.0	9.5	8.0	15.1	14.3	508.0	33.3	57.1	89.6
500	400	20	16	508.0	406.4	5.5	5.0	9.5	8.0	15.1	12.7	508.0	31.6	54.2	85.1
500	350	20	14	508.0	355.6	5.5	5.0	9.5	8.0	15.1	11.1	508.0	30.0	51.4	80.7
500	300	20	12	508.0	318.5	5.5	4.5	9.5	6.5	15.1	10.3	508.0	28.9	49.5	77.5
500	500	20	20	558.8	508.0	5.5	5.5	9.5	9.5	15.9	15.1	508.0	36.8	63.2	104.5
550	450	22	18	558.8	457.2	5.5	5.0	9.5	8.0	15.9	14.3	508.0	35.2	60.3	99.7
550	400	22	16	558.8	406.4	5.5	5.0	9.5	8.0	15.9	12.7	508.0	33.6	57.6	95.1
550	350	22	14	558.8	355.6	5.5	5.0	9.5	8.0	15.9	11.1	508.0	32.1	55.0	90.7
550	550	22	22	609.6	558.8	6.5	5.5	9.5	9.5	17.5	15.9	508.0	47.6	69.3	125.9
600	500	24	20	609.6	508.0	6.5	5.5	9.5	9.5	17.5	15.1	508.0	45.7	66.5	120.7
600	450	24	18	609.6	457.2	6.5	5.0	9.5	8.0	17.5	14.3	508.0	43.9	63.8	115.8
600	400	24	16	609.6	406.4	6.5	5.0	9.5	8.0	17.5	12.7	508.0	42.1	61.2	111.0
650	600	26	24	660.4	609.6	8.0	6.5	12.7	9.5	—	—	609.6	76.3	120.4	—
650	550	26	22	660.4	558.8	8.0	5.5	12.7	9.5	—	—	609.6	73.4	115.7	—
650	500	26	20	660.4	508.0	8.0	5.5	12.7	9.5	—	—	609.6	70.6	111.3	—
650	450	26	18	660.4	457.2	8.0	5.0	12.7	8.0	—	—	609.6	67.9	107.0	—
650	650	26	26	711.2	660.4	8.0	8.0	12.7	12.7	—	—	609.6	82.5	130.2	—
700	600	28	24	711.2	609.6	8.0	6.5	12.7	9.5	17.5	17.5	609.6			