


溶接キャップ CAP

単位:mm



呼び径		外径	背から端面 までの距離	厚み					
				Sch10S		Sch20S		Sch40	
(A)	(B)	OD	E	内径	厚み	内径	厚み	内径	厚み
10	$\frac{3}{8}$	17.3	20.0	14.9	1.2	14.0	1.7	12.7	2.3
15	$\frac{1}{2}$	21.7	25.4	17.5	2.1	16.7	2.5	16.1	2.8
20	$\frac{3}{4}$	27.2	25.4	23.0	2.1	22.2	2.5	21.4	2.9
25	1	34.0	38.1	28.4	2.8	28.0	3.0	27.2	3.4
32	$1\frac{1}{4}$	42.7	38.1	37.1	2.8	36.7	3.0	35.5	3.6
40	$1\frac{1}{2}$	48.6	38.1	43.0	2.8	42.6	3.0	41.2	3.7
50	2	60.5	38.1	54.9	2.8	53.5	3.5	52.7	3.9
65	$2\frac{1}{2}$	76.3	38.1	70.3	3.0	69.3	3.5	65.9	5.2
80	3	89.1	50.8	83.1	3.0	81.1	4.0	78.1	5.5
90	$3\frac{1}{2}$	101.6	63.5	95.6	3.0	93.6	4.0	90.2	5.7
100	4	114.3	63.5	108.3	3.0	106.3	4.0	102.3	6.0
125	5	139.8	76.2	133.0	3.4	129.8	5.0	126.6	6.6
150	6	165.2	88.9	158.4	3.4	155.2	5.0	151.0	7.1
200	8	216.3	101.6	208.3	4.0	203.3	6.5	199.9	8.2
250	10	267.4	127.0	259.4	4.0	254.4	6.5	248.8	9.3
300	12	318.5	152.4	309.5	4.5	305.5	6.5	297.9	10.3
350	14	355.6	165.1	345.6	5.0	339.6	8.0	333.4	11.1
400	16	406.4	177.8	396.4	5.0	390.4	8.0	381.0	12.7
450	18	457.2	203.2	447.2	5.0	441.2	8.0	428.6	14.3
500	20	508.0	228.6	497.0	5.5	489.0	9.5	477.8	15.1
550	22	558.8	254.0	547.8	5.5	539.8	9.5	527.0	15.9
600	24	609.6	266.7	596.6	6.5	590.6	9.5	574.6	17.5
650	26	660.4	266.7	644.4	8.0	635.0	12.7	—	—