


180°ロングエルボ 180E (L)

単位:mm

単位:kg



呼び径		外径	厚み			中心から中心 までの距離	背から端面ま での距離
(A)	(B)	OD	Sch10S	Sch20S	Sch40	P	K
10	$\frac{3}{8}$	—	—	—	—	—	—
15	$\frac{1}{2}$	21.7	2.1	2.5	2.8	76.2	49.0
20	$\frac{3}{4}$	27.2	2.1	2.5	2.9	76.2	51.7
25	1	34.0	2.8	3.0	3.4	76.2	55.1
32	$1\frac{1}{4}$	42.7	2.8	3.0	3.6	95.2	69.0
40	$1\frac{1}{2}$	48.6	2.8	3.0	3.7	114.4	81.5
50	2	60.5	2.8	3.5	3.9	152.4	106.5
65	$2\frac{1}{2}$	76.3	3.0	3.5	5.2	190.6	133.5
80	3	89.1	3.0	4.0	5.5	228.6	158.9
90	$3\frac{1}{2}$	101.6	3.0	4.0	5.7	266.8	184.2
100	4	114.3	3.0	4.0	6.0	304.8	209.6
125	5	139.8	3.4	5.0	6.6	381.0	260.4
150	6	165.2	3.4	5.0	7.1	457.2	311.2
200	8	216.3	4.0	6.5	8.2	609.6	413.0

概略重量		
Sch10S	Sch20S	Sch40
—	—	—
0.1	0.1	0.2
0.2	0.2	0.2
0.3	0.3	0.3
0.4	0.4	0.5
0.6	0.6	0.7
1.0	1.2	1.3
1.6	1.9	2.8
2.3	3.1	4.1
3.1	4.1	5.7
4.0	5.3	7.8
6.9	10.1	13.1
9.9	14.4	20.1
20.3	32.6	40.8