

水道用フランジ 2種 F12(上水形) JIS G 3443-2-2014



大平面座形 (RF 形)

溝形 (GF 形)


呼び径 (A) 80 ~ 3000



大平面座形 (RF 形) 開先 溝形 (GF 形)




GF 形ガスケット1号用




GF 形ガスケット2号用

開先詳細


■ V 形外開先 (呼び径 (A) 700A 以下)



■ V 形内開先 (呼び径 (A) 800A 以上で厚み 16 未満)



■ X 形開先 (呼び径 (A) 800A 以上で厚み 16 以上)

a: 2 以下
b: 2/3(t-a)
c: 1/3(t-a)

単位:mm

呼び径		外径	内径	厚み	座厚	座径	全長	ハブ先の径	ハブ厚	すみ径	ボルト穴			ガスケット溝			重量 (kg)	
(A)	(B)	D5	B	K	M	D3	L	D2	T	r	中心径 D4	数	d'	G	e	S	RF 形	GF 形
80	3	211	80.7	18	2	125	40	89.1	8	5	168	4	19	90	10	5	4.01	3.89
100	4	238	105.3	18	2	152	45	114.3	9	5	195	4	19	115	10	5	5.01	4.86
125	5	263	130.8	20	2	177	45	139.8	9	5	220	6	19	145	10	5	6.30	6.11
150	6	290	155.2	22	2	204	50	165.2	10	5	247	6	19	170	10	5	8.21	7.99
200	8	342	204.7	22	2	256	55	216.3	11	5	299	8	19	220	10	5	10.7	10.4
250	10	410	254.2	24	2	308	60	267.4	13	5	360	8	23	275	10	5	16.2	15.8
300	12	464	304.7	24	3	362	70	318.5	15	5	414	10	23	325	10	5	19.9	19.5
350	14	530	343.6	26	3	414	85	355.6	17	5	472	10	25	375	10	5	29.3	28.8
400	16	582	394.4	26	3	466	95	406.4	19	5	524	12	25	425	10	5	34.9	34.3
450	18	652	445.2	28	3	518	105	457.2	21	6	585	12	27	475	10	5	46.9	46.3
500	20	706	496.0	28	3	572	105	508.0	21	6	639	12	27	530	10	5	52.4	51.7
600	24	810	597.6	30	3	676	110	609.6	22	6	743	16	27	630	10	5	66.9	66.1
700	28	928	697.2	32	3	780	130	711.2	24	7	854	16	33	730	10	5	93.3	92.4
			699.2														92.0	91.1
800	32	1034	796.8	34	3	886	130	812.8	25	7	960	20	33	833	10	5	114	113
			798.8														112	111
900	36	1156	898.4	36	3	990	150	914.4	27	7	1073	20	33	935	10	5	152	151
			900.4														150	149
1000	40	1262	998.0	38	3	1096	150	1016.0	28	8	1179	24	33	1032	16	8	179	176
			1000.0														177	174
1100	44	1366	1097.6	41	3	1200	170	1117.6	31	8	1283	24	33	1134	16	8	227	223
			1101.6														221	218
1200	48	1470	1197.2	43	3	1304	170	1219.2	32	9	1387	28	33	1236	16	8	260	256
			1201.2														254	250
1350	54	1642	1347.6	45	3	1462	180	1371.6	34	9	1552	28	39	1390	16	8	329	324
			1351.6														321	317
1500	60	1800	1496.0	48	3	1620	190	1524.0	36	10	1710	32	39	1544	16	8	406	401
			1502.0														393	388
1600	64	1915	1595.6	53	3	1760	210	1625.6	40	11	1820	36	39	1656	24	12	513	501
			1601.6														498	486
1650	66	1965	1646.4	53	3	1810	210	1676.4	40	11	1870	40	39	1708	24	12	526	514
			1652.4														510	498
1800	72	2115	1796.8	55	3	1960	210	1828.8	41	11	2020	44	39	1856	24	12	589	576
			1802.8														576	562
2000	80	2325	1996.0	58	4	2170	220	2032.0	43	11	2230	48	46	2061	24	12	706	691
			2002.0														686	671
2100	84	2430	2095.6	59	4	2270	220	2133.6	44	12	2335	48	46	2161	24	12	765	750
			2101.6														744	728
2200	88	2550	2195.2	61	4	2370	240	2235.2	46	12	2440	52	46	2261	24	12	899	883
			2203.2														867	851
2300	92	2640	2294.8	62	4	2470	240	2336.8	46	12	2545	52	46	2361	24	12	934	917
			2302.8														901	884
2400	96	2760	2394.4	64	4	2570	240	2438.4	48	13	2650	56	46	2461	24	12	1050	1030
			2402.4														1010	993
2500	100	2855	2494.0	68	5	2680	260	2540.0	51	13	2755	56	52	2562	28	14	1170	1140
			2504.0														1120	1090
2600	104	2960	2593.6	68	5	2780	260	2641.6	51	13	2850	56	52	2662	28	14	1230	1210
			2603.6														1180	1160
2700	108	3080	2693.2	71	5	2880	270	2743.2	53	14	2970	60	52	2762	28	14	1400	1370
			2703.2														1350	1320
2800	112	3180	2794.8	72	5	3000	270	2844.8	54	14	3070	60	52	2872	28	14	1470	1440
			2804.8														1410	1380
3000	120	3405	2994.0	76	5	3210	290	3048.0	58	15	3290	64	52	3072	28	15	1800	1770
			3004.0														1740	1710